

OT200

Palmare Comanda



OT-200

# Caratteristiche tecniche

CPU: Samsung S3C6410 667 MHz processor  
Operating System Microsoft® Windows™ Mobile 6.5 Professional  
Display 4.3" TFT LCD with Touch Screen, widescreen 800\*480  
Memory 256MB Flash, 256MB SDRAM  
Communication WLAN 802.11b/g  
Telecom standards (option) GPRS/EDGE  
GPS (option) Atheros  
Extension slot microSD card (supports SDHC)  
Interface Mini-USB 2.0  
Other G-sensor (for auto-rotation) Speaker  
Vibrator motor (for alerts) Earphone jack (3.5mm)  
Internal microphone Microphone jack (2.5mm)  
Features Wireless roaming  
SSID Lock  
Battery cover safety protection  
Remote Desktop  
Lock screen  
Ruggedness IP54  
1.2 meters drop tested  
Environmental Operating temperature: 0 °C to 40 °C  
Storage temperature: -20 °C to 60 °C  
Battery Rechargeable Li-ion battery 2300mAh (removable)  
Dimensions (WxLxH) 82 \* 133 \* 19 mm  
Weight Approximately 245g with battery  
Optional modules RFID module (Mifare 13.56 MHz)  
MSR module (Track 1, 2, 3)  
Barcode scanner module(1D)  
Accessories AC adaptor, Battery, High quality stylus, Stylus cord, Hand strap  
(Option: Leather pouch, Leather pouch cord, Shoulder strap, Cradle)  
Certifications RF: FCC / CE / SRRC / NCC (for WiFi 802.11b/g, Bluetooth, RFID)  
EMC: FCC / CE / 3C / BSMI / VCCI  
Safety: 3C / BSMI / CB (IEC60950-1:2005 / EN60950-1:2001, 1st ed.)



# OT-200