

SP-1000

Soluzioni PC POS



SP-1000



# Caratteristiche tecniche

CPU Type Intel® Atom™ processor D525  
(1M L2 Cache, 1.80 GHz, dual core )  
LCD 15" active color TFT-LCD, resolution 1024 x 768  
Touch 5-wire resistive touch (PS/2 interface)  
Memory 204pin DDR3 SO-DIMM 1GB (2 DIMM Sockets up to 4 GB)  
LAN IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet  
Storage Internal 2.5" type SATA HDD 160GB, Support 2nd HDD (optional)  
I/O Interface 6 x COM ports  
(COM1~4 at back I/O, COM5 reserved, COM6 for VFD)  
1 x DB-15 VGA port  
1 x DB-25 for LPT port  
1 x RJ-11 port for 2 cash drawer (+24V)  
1 x RJ-45 LAN port with activity and link LEDs  
2 x Audio ports (1 x Line-out , 1 x MIC-in)  
8 x USB 2.0 (4 x in the back, 1 x for Mini-PCI-e,  
1 x for MSR+RFID reader, 2 x reserve)  
1 x DC +12V power adaptor connector  
Operation System Windows 7, Windows XP, XPe,  
Linux (ubuntu, Fedora), WEPOS, POSReady  
LCD Brightness 250 cd/m2 (w/o touch)  
Power Supply AC 100~240V/DC 12V, 7.5A, 90 watt power adaptor  
Dimensions 360 mm (W) x 240 mm (D) x 365 mm (H), (LCD 15 tilt angle)  
Certification CE/FCC Class B, cUL, VCCI, BSMI  
Periferiche opzionali: 3-track Magnetic reader, Customer display (2x20 VFD)



# SP-1000